


- Fiber Optic Splice Closure
- Fiber Optic Termination/Terminal Box (Indoor)**
  - o Fiber Optic Outlet
  - o Fiber Optic Floor Terminal Box
  - o Big capacity Fiber optic terminal box
- Fiber Optic Distribution Box (Outdoor)
- Fiber Optic Connectivity
- PLC Splitter
- Accessories

**Newsletter for wholesale**

Subscribe free newsletter to get latest products and discount information.

Home >> Fiber Optic Termination/Terminal Box (Indoor) >> Fiber Optic Outlet



## Fiber optic outlet standard 86 | GP-T861

Item No.: GP-T861  
 Dimensions: 86x86x21.5 mm  
 Max. adapters: 2 SC  
 Splice capacity: 2 FO

### . Application

. Wall mounted termination box for end user, indoor use, capable to handle fiber fusion, fiber cables and pigtailed.

### . Specifications

--	--	--



Parameter	Value	Remark
Model	GP-T861	
Dimension (mm)	86x86x21.5	
Material	Plastic	
Color	RAL9001	
Storage of fibers	G.657 A1, G.657B3	
Splice capacity	1/2 FO	
Splice Method	Fusion Splice	45mm sleeve applied
Adaptor Type	SC	
No. of Adaptor	2	
Max. diameter of drop cable	5mm	


[Home](#)
[News](#)
[Feedback](#)
[Products](#)

pe wrapping film    galvanized c purlin steel

NINGBO FIBERMINT TELECOM EQUIPMENT CO., LTD.